



Professional laundry

Professional washer extractors

**PROFESSIONAL WASHER EXTRACTOR,  
PW-6 P**

**DIMENSIONS**

		Article	Packed
Length	mm	595,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	73,00	77,00
Volumen	m3	0,30	0,53

**ELECTRICITY**

Electric power	KW	
230V - 1+N		2x2,5 + T -25A
230V - III		
400V - III+N		4x1,5+T - 10A

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used

**AIR**


Not used

**PROFESSIONAL WASHER EXTRACTOR, PW-6 P**

Soft mount high spin washer extractor.  
530 G factor (at 1400 rpm).  
Stainless steel construction  
Door: true metal frame, 180° opening, double insulated glass.  
Drum in stainless steel, removable lifters, gentle area evacuation holes  
Microprocessor: fixed programs. Mop and microfiber programs. Service menu.  
Balance control.  
Electric heating: stainless steel elements.  
Detergent compartment: prepared for chemicals for external dosing system.  
Model with drain pump.  
Capacity: 6 kg.  
Basket volume: 60 litres.  
Drum: Ø 480 mm.  
Spin speed: 1,400 rpm.  
G factor: 530.  
Heating element: 3.2 kW.  
Electrical connection: 400 V - 3+N / 230 V - 1+N.  
Power: 3,8 kW  
Dimensions: 600 x 585 x 850 mm.

Available dryer for stacking assembly (PD-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		0
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	





Professional laundry

Professional washer extractors

**PROFESSIONAL WASHER EXTRACTOR,  
PW-6 V**

**DIMENSIONS**

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	73,00	77,00
Volumen	m3	0,30	0,53

**ELECTRICITY**

Electric power	KW	
230V - 1+N		2x2,5 + T -25A
230V - III		
400V - III+N		4x1,5+T - 10A

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used

**AIR**


Not used

**PROFESSIONAL WASHER EXTRACTOR, PW-6 V**

Soft mount high spin washer extractor.  
530 G factor (at 1400 rpm).  
Stainless steel construction  
Door: true metal frame, 180° opening, double insulated glass.  
Drum in stainless steel, removable lifters, gentle area evacuation holes  
Microprocessor: fixed programs. Mop and microfiber programs. Service menu.  
Balance control.  
Electric heating: stainless steel elements.  
Detergent compartment: prepared for chemicals for external dosing system.  
Model with drain valve.  
Capacity: 6 kg.  
Basket volume: 60 litres.  
Drum: Ø 480 mm.  
Spin speed: 1,400 rpm.  
G factor: 530.  
Heating element: 3.2 kW.  
Electrical connection: 400 V - 3+N / 230 V - 1+N.  
Power: 3,8 kW  
Dimensions: 600 x 585 x 850 mm.

Available dryer for stacking assembly (PD-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		0
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	





Professional laundry

Professional washer extractors

## PROFESSIONAL WASHER EXTRACTOR, PW-8 P

### DIMENSIONS

		Article	Packed
Length	mm	595,00	610,00
Depth	mm	726,00	800,00
Height	mm	850,00	915,00
Weigth	Kg	92,00	96,00
Volumen	m3	0,37	0,53

### ELECTRICITY

Electric power	KW	
230V - 1+N		2x2,5 + T -25A
230V - III		
400V - III+N		4x1,5+T - 10A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL WASHER EXTRACTOR, PW-8 P

Soft mount high spin washer extractor.

530 G factor (at 1400 rpm).

Stainless steel construction

Door: true metal frame, 180° opening, double insulated glass.

Drum in stainless steel, removable lifters, gentle area evacuation holes

Microprocessor: fixed programs. Mop and microfiber programs. Service menu.

Balance control.

Electric heating: stainless steel elements.

Detergent compartment: prepared for chemicals for external dosing system.

Model with drain pump.

Capacity: 8 kg.

Basket volume: 80 litres.

Drum: Ø 480 mm.

Spin speed: 1,400 rpm.

G factor: 530.

Heating element: 3.2 kW.


Electrical connection: 400 V - 3+N / 230 V - 1+N.

Power: 3,8 kW

Dimensions: 600 x 726 x 850 mm.

Available dryer for stacking assembly (PD-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		0
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-6 V

### DIMENSIONS

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	39,00	45,00
Volumen	m3	0,30	0,53

### ELECTRICITY

Electric power	KW	
230V - 1+N		2x1,5 + T -16A
230V - III		NO
400V - III+N		4x1,5 + T - 6A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR


Not used

### PROFESSIONAL TUMBLE DRYER, PD-6 V

Sturdy construction.  
 Drum on two support rollers.  
 Magnetic door lock.  
 Reversing door.  
 Double lint filter with display reminder.  
 Temperature sensor, ideal for the most sensitive clothes and to reduce energy consumption  
 Programmer: 7 fixed sensor controlled programs.  
 Air exhaust system.  
 Capacity: 6,2 Kg.  
 Drum: Ø 571 x 476 mm depth.  
 Volume: 112 litres.  
 Air evacuation Ø: 100 mm.  
 Airflow: 300 m3/h.  
 Electrical connection: 400 V - 3+N // 230 V - 1+N.  
 Power: 3 KW  
 Dimensions: 600 x 585 x 850 mm

Available washer extractor for stacking assembly (PW-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	100	0	700		0
EXHAUST	290	0	110	100 mm	300 m3/h





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-6 C

### DIMENSIONS

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	39,00	45,00
Volumen	m3	0,30	0,53

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5 + T -16A
230V - III		NO
400V - III+N		4x1,5 + T - 6A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-6 C

Sturdy construction.

Drum on two support rollers.

Magnetic door lock.

Reversing door.

Double lint filter with display reminder.

Temperature sensor, ideal for the most sensitive clothes and to reduce energy consumption

Programmer: 7 fixed sensor controlled programs.

Condenser model: the air is warmed up when passing through a heater.

Moist is collected as water drops in the condenser and is evacuated either via drain hose or gathered in a water tank.

Capacity: 6,2 Kg.

Drum: Ø 571 x 476 mm depth.

Volume: 112 litres.

Air evacuation Ø: 100 mm.

Airflow: 300 m3/h.


Electrical connection: 400 V - 3+N // 230 V - 1+N.

Power: 2,5 kW

Dimensions: 600 x 585 x 850 mm

Available washer extractor for stacking assembly (PW-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	100	0	700		0
EXHAUST	290	0	110	100 mm	300 m3/h





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-6 HP

### DIMENSIONS

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	39,00	45,00
Volumen	m3	0,30	0,53

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5 + T - 6 A
230V - III		
400V - III+N		

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-6 HP

Sturdy construction.

Drum on two support rollers.

Magnetic door lock.

Reversing door.

Double lint filter with display reminder.

Temperature sensor, ideal for the most sensitive clothes and to reduce energy consumption

Programmer: 7 fixed sensor controlled programs.

Heat pump dryer: no extra external air needed. The air is heated in the condenser. The air runs through the drum, transporting moist air out of the drum. Moist air is condensed in the evaporator and is evacuated through an attached exhaust pipe, or led to condense water tank. It has

Capacity: 6,2 Kg.

Drum: Ø 571 x 476 mm depth.

Volume: 112 litres.

Air evacuation Ø: 100 mm.

Airflow: 300 m3/h.


Electrical connection: 230 V - 1+N.

Power: 0,8 kW

Dimensions: 600 x 585 x 850 mm

Available washer extractor for stacking assembly (PW-6).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	100	0	700		0
EXHAUST	290	0	110	100 mm	300 m3/h





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-8 V

### DIMENSIONS

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	726,00	800,00
Height	mm	850,00	915,00
Weigth	Kg	45,00	50,00
Volumen	m3	0,37	0,60

### ELECTRICITY

Electric power	KW	
230V - 1+N		2x1,5 + T -16A
230V - III		NO
400V - III+N		4x1,5 + T - 6A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-8 V

Sturdy construction.

Drum on two support rollers.

Magnetic door lock.

Reversing door.

Double lint filter with display reminder.

Temperature sensor, ideal for the most sensitive clothes and to reduce energy consumption

Programmer: 7 fixed sensor controlled programs.

Air exhaust system.

Capacity: 8 Kg.

Drum: Ø 571 x 476 mm depth.

Volume: 145 litres.

Air evacuation Ø: 100 mm.

Airflow: 300 m3/h.


Electrical connection: 400 V - 3+N // 230 V - 1+N.

Power: 3 kW

Dimensions: 600 x 726 x 850 mm

Available washer extractor for stacking assembly (PW-8).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	100	0	700		0
EXHAUST	290	0	110	100 mm	300 m3/h





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-8 HP

### DIMENSIONS

		Article	Packed
Length	mm	600,00	610,00
Depth	mm	585,00	660,00
Height	mm	850,00	915,00
Weigth	Kg	39,00	45,00
Volumen	m3	0,30	0,53

### ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5 + T - 6 A
230V - III		
400V - III+N		

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-8 HP

Sturdy construction.

Drum on two support rollers.

Magnetic door lock.

Reversing door.

Double lint filter with display reminder.

Temperature sensor, ideal for the most sensitive clothes and to reduce energy consumption

Programmer: 7 fixed sensor controlled programs.

Heat pump dryer: no extra external air needed. The air is heated in the condenser. The air runs through the drum, transporting moist air out of the drum. Moist air is condensed in the evaporator and is evacuated through an attached exhaust pipe, or led to condense water tank. It has

Capacity: 8 Kg.

Drum: Ø 571 x 476 mm depth.

Volume: 145 litres.

Air evacuation Ø: 100 mm.

Airflow: 300 m3/h.


Electrical connection: 230 V - 1+N.

Power: 0,9 kW

Dimensions: 600 x 726 x 850 mm

Available washer extractor for stacking assembly (PW-8).

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	100	0	700		0
EXHAUST	290	0	110	100 mm	300 m3/h







Professional laundry

Professional washer extractors

## PROFESSIONAL WASHER EXTRACTOR, PW-10

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	704,00	730,00
Height	mm	1.027,00	1.300,00
Weigth	Kg	113,00	123,00
Volumen	m3	0,49	0,67

### ELECTRICITY

Electric power	KW	
230V -1+N		2x4+T-32A
230V - III		3x2,5+T - 20A
400V - III+N		4x1,5+T - 16A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL WASHER EXTRACTOR, PW-10

External case made in white varnished steel.

Stainless steel wash basket and outer tub.

Four shock absorbers.

Electronic programmable controls.

Cycle time: 31 - 35 minutes (without heating time).

Capacity: 9.68 kg.

Basket volume: 96.8 litres.

Drum diameter: Ø 395 mm.

Spin speed: 1,200 rpm. G factor: 440.

Motor with variable speed induction and thermal protection.

Drain pump.


Heating element: 4,8 Kw.

Maximum power: 5.5 Kw.

Maximun power: 5,5 KW.

Dimensions; 683 x 704 x 1.027 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	





Professional laundry

Professional washer extractors

**PROFESSIONAL WASHER EXTRACTOR,  
PW-10 INOX**

**DIMENSIONS**

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	704,00	730,00
Height	mm	1.027,00	1.300,00
Weigth	Kg	113,00	123,00
Volumen	m3	0,49	0,67

**ELECTRICITY**

Electric power	KW	
230V -1+N		2x4+T-32A
230V - III		3x2,5+T - 20A
400V - III+N		4x1,5+T - 16A

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used


**AIR**

Not used

PROFESSIONAL WASHER EXTRACTOR, PW-10 INOX

External case made in stainless steel.  
Stainless steel wash basket and outer tub.  
Four shock absorbers.  
Electronic programmable controls.  
Cycle time: 31 - 35 minutes (without heating time).  
Capacity: 9.68 kg.  
Basket volume: 96.8 litres.  
Drum diameter: Ø 395 mm.  
Spin speed: 1,200 rpm. G factor: 440.  
Motor with variable speed induction and thermal protection.  
Drain pump.  
Heating element: 4,8 Kw.  
Maximum power: 5.5 Kw.  
Maximum power: 5,5 KW.  
Dimensions; 683 x 704 x 1.027 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	895		
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-10 M

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	711,00	730,00
Height	mm	1.092,00	1.300,00
Weigth	Kg	60,00	70,00
Volumen	m3	0,53	0,67

### ELECTRICITY

Electric power	KW	
230V -1+N		2x4 + T - 32 A
230V - III		3x2,5+T-20A
400V - III+N		4x1,5+T-16A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-10 M

Enamelled external case, white color.

5 programs.

Program for cold drying.

Timer and final cooling cycle.

Fluff filter in lower part.

Safety door switch.

Models with white lacquered steel external case: control board at the rear part.

Models with external case made in stainless steel: control board on the front panel.

Capacity: 10.5 kg.

Volume: 201 l.

Drum: Ø 670 x 564 mm.


Heating power: 5.35 kW.

Maximum power: 5.6 kW.

Single-phase model - Connection: 230 V -1+N.

Dimensions: 683 x 711 x 1.092 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	220	0	700		
EXHAUST	410	0	110	100	





Professional laundry

Professional dryers

## PROFESSIONAL TUMBLE DRYER, PD-10 T

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	711,00	730,00
Height	mm	1.092,00	1.300,00
Weigth	Kg	60,00	70,00
Volumen	m3	0,53	0,67

### ELECTRICITY

Electric power	KW	
230V -1+N		
230V - III		3x2,5+T-20A
400V - III+N		4x1,5+T-16A

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### PROFESSIONAL TUMBLE DRYER, PD-10 T

Enamelled external case, white color.

5 programs.

Program for cold drying.

Timer and final cooling cycle.

Fluff filter in lower part.

Safety door switch.

Models with white lacquered steel external case: control board at the rear part.

Models with external case made in stainless steel: control board on the front panel.

Capacity: 10.5 kg.

Volume: 201 l.

Drum: Ø 670 x 564 mm.


Heating power: 5.35 kW.

Maximum power: 5.6 kW.

Connection: 400 V -3+N.

Dimensions: 683 x 711 x 1.092 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	220	0	700		
EXHAUST	410	0	110	100	





Professional laundry

Professional dryers

**PROFESSIONAL TUMBLE DRYER,  
PD-10-INOX**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>683,00</b>	<b>700,00</b>
Depth	mm	<b>711,00</b>	<b>730,00</b>
Height	mm	<b>1.027,00</b>	<b>1.300,00</b>
Weigth	Kg	<b>60,00</b>	<b>70,00</b>
Volumen	m3	<b>0,50</b>	<b>0,67</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>2x4 + T - 32 A</b>
230V - III		<b>3x2,5+T-20A</b>
400V - III+N		<b>4x1,5+T-16A</b>

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

PROFESSIONAL TUMBLE DRYER, PD-10 INOX

External case made in stainless steel.

5 programs.

Program for cold drying.

Timer and final cooling cycle.

Fluff filter in lower part.

Safety door switch.

Models with white lacquered steel external case: control board at the rear part.

Models with external case made in stainless steel: control board on the front panel.

Capacity: 10.5 kg.

Volume: 201 l.

Drum: Ø 670 x 564 mm.


Heating power: 5.35 kW.

Maximum power: 5.6 kW.

Connection: 400 V -3+N.

Dimensions: 683 x 711 x 1.126 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	220	0	700		
EXHAUST	410	0	110	100	





Professional laundry

Stack washer-dryer

## STACK WASHER / DRYER, PWD-10

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	711,00	730,00
Height	mm	1.986,00	2.200,00
Weigth	Kg	163,00	177,00
Volumen	m3	0,96	1,13

### ELECTRICITY

Electric power	KW	
230V -1+N		10,70
230V - III		
400V - III+N	4x2.5+T - 20 A	

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### STACK WASHER / DRYER, PWD-10

Stacking unit including Washer and dryer.

External case made in white varnished steel.

Connection: 400 V - III+N

Dimensions of the stacking assembly: 683 x 711 x 1.986 mm.

#### WASHER EXTRACTOR:

Stainless steel wash basket and outer tub.

Four shock absorbers.

Capacity: 9.68 kg.

Electronic programmable controls.

Cycle time: 31 - 35 minutes (without heating time).

Basket volume: 96.8 litres.

Door diameter: Ø 395 mm.

Spin speed: 1,200 rpm. G factor: 440.

Motor with variable speed induction and thermal protection.

Drain pump.

Heating element: 4,8 kW.

Maximum power: 5.5 kW.

#### TUMBLE DRYER:

Capacity: 9,9 kg.

5 programs.

Program for cold drying.

Timer and final cooling cycle.

Fluff filter in lower part.

Safety door switch.


Models with white lacquered steel external case: control board at the rear part

Models with external case made in stainless steel: control board on the front panel

Heating power: 5.35 kW.

Maximum power: 5.6 kW.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	1.500		
ELECTRICITY	575	0	895		0
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	
EXHAUST	290	0	1.100	100	





Professional laundry

Stack washer-dryer

## STACK WASHER / DRYER, PWD-10 INOX

### DIMENSIONS

		Article	Packed
Length	mm	683,00	700,00
Depth	mm	711,00	730,00
Height	mm	1.986,00	2.200,00
Weigth	Kg	163,00	177,00
Volumen	m3	0,96	1,13

### ELECTRICITY

Electric power	KW	
230V -1+N		10,70
230V - III		
400V - III+N	4x2.5+T - 20 A	

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

STACK WASHER / DRYER, PWD-10 INOX

Stacking unit including Washer and dryer.

External case made in stainless steel.

Connection: 400 V - III+N

Dimensions of the stacking assembly: 683 x 711 x 1.986 mm.

#### WASHER EXTRACTOR:

Stainless steel wash basket and outer tub.

Four shock absorbers.

Capacity: 9.68 kg.

Electronic programmable controls.

Cycle time: 31 - 35 minutes (without heating time).

Basket volume: 96.8 litres.

Door diameter: Ø 395 mm.

Spin speed: 1,200 rpm. G factor: 440.

Motor with variable speed induction and thermal protection.

Drain pump.

Heating element: 4,8 kW.

Maximum power: 5.5 kW.

#### TUMBLE DRYER:

Capacity: 9,9 kg.

5 programs.

Program for cold drying.

Timer and final cooling cycle.

Fluff filter in lower part.

Safety door switch.

Models with white lacquered steel external case: control board at the rear part

Models with external case made in stainless steel: control board on the front panel

Heating power: 5.35 kW.

Maximum power: 5.6 kW.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	575	0	1.500		
ELECTRICITY	575	0	895		0
DRAIN	110	0	90	25 mm	
COLD WATER	100	0	780	3/4"	
HOT WATER	100	0	740	3/4"	
EXHAUST	290	0	1.100	100	

